

# AQ Guard Ambient



Compact ambient air quality monitor. Featuring Palas® aerosol spectrometer technology for precise measurement of air pollution by particulates.

## Benefits

- Technology based on the type approved Fidas® 200 series (EN16450 and MCERTS); simultaneous measurement of Cn, PM1, PM2.5, PM4, PM10
- Computation of air quality index based on measurements of particulates, CO2, and VOC
- High accuracy due to advanced algorithms
- Long term stable due to self calibration for measurement of flow rate, particulates, and gaseous pollutants
- 2 years operation without calibration; recalibration with NIST traced test powder possible on site
- Operates on AC, DC, or power-over-Ethernet

## Applications

- Industry:
  - Production processes
  - Bulk material handling (mixing, discharge, storage, packaging etc.)
  - Fenceline Monitoring
- Construction sites: Roads, railroads, demolition sites
- Buildings: Schools, kindergartens, hospitals, hotels, offices, public service buildings
- Residential buildings near construction sites or other polluted areas
- Public transportation: Airports, train stations, tramway underground stations, cruise ships, passenger cabin, e.g. in tram, train



<https://www.palas.de/product/aq-guard-ambient>

# AQ Guard Ambient



## Datasheet

Parameter	Description
<b>Interfaces</b>	USB, Ethernet, Wi-Fi, optional: UMTS
<b>Measurement range (size)</b>	0.175 – 20 µm
<b>Size channels</b>	128 (64/decade)
<b>Measuring principle</b>	Single particle optical light scattering with evaluation of signal duration and shape, advanced mass conversion algorithm
<b>Measurement range (number C<sub>N</sub>)</b>	0 – 20,000 particles/cm <sup>3</sup>
<b>Volume flow</b>	1.0 l/min $\hat{=}$ 0.06 m <sup>3</sup> /h
<b>Data acquisition</b>	Digital, 22 MHz processor, 256 raw data channels
<b>Light source</b>	Long term stable LED
<b>Power consumption</b>	< 60 W
<b>User interface</b>	Touchscreen 800 • 480 pixels, 5" ( 12,7cm )
<b>Dimensions</b>	240 • 320 • 190 • mm ( H • W • D )
<b>Weight</b>	3.9 kg
<b>Operating system</b>	Windows 10 IoT Enterprise
<b>Data logger storage</b>	10 GB
<b>Software</b>	PDAnalyze
<b>Response time</b>	1 s
<b>Aerosol conditioning</b>	Thermal with compact IADS
<b>Measurement range (mass)</b>	0 – 20,000 µg/m <sup>3</sup>
<b>Reported data</b>	PM <sub>1</sub> , PM <sub>2.5</sub> , PM <sub>4</sub> , PM <sub>10</sub> , TSP, C <sub>N</sub> , particle size distribution, pressure, temperature, relative humidity, CO <sub>2</sub> , TVOC, Air Quality Index
<b>Installation conditions</b>	-20 – +50 °C, weatherproof
<b>Linearity</b>	0.95 – 1.05 (measured against EN16450 certified Fidas® 200)
<b>Accuracy</b>	R <sub>2</sub> > 0,98 for PM <sub>2.5</sub> and R <sub>2</sub> > 0,94 for PM <sub>10</sub> versus EN16450-certified Fidas® 200 (15 min average, each)

**Palas GmbH**  
Partikel- und Lasermesstechnik  
Greschbachstrasse 3 b  
76229 Karlsruhe  
Germany

**Managing Partner:**  
Dr.-Ing. Maximilian Weiß  
**Commercial Register:**  
register court: Mannheim  
company registration number: HRB 103813  
USt-Id: DE143585902



**Contact:** E-Mail: [mail@palas.de](mailto:mail@palas.de) Internet: [www.palas.de](http://www.palas.de) Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33