



Powder disperser with dispersing nozzle and weighing unit for low mass flows of approx. $8\,g/h$ – $550\,g/h$; automatic mass flow monitoring and control

Description

This dispersion system is able to continuously generate low mass flows, e.g. 8 g/h, with optimal dosing constancy and control with automatic mass flow monitoring. Mass flow setting of approx. 8 g/h - 550 g/h based on SAE fine, A2 dust

Version: September 3, 2020

BEG 2000 A



Benefits

- Excellent short-term and long-term dosing constancy
- Easy to operate
- Quick and easy to clean
- Remote control or computer-controlled
- Pulse mode
- Easy to fill while in operation
- Large reservoir (1500 cm³)
- Automatic mass flow control with the BEG 2000
- Robust design, proven in industrial applications
- Reliable function
- Reduces your operating expenses
- Low maintenance

Version: September 3, 2020

BEG 2000 A



Datasheet

Parameter	Description
Volume flow	
	5 – 10 m ³ /h
Power supply	
	115 – 230 V, 50 – 60 Hz
Particle material	
Dosing time	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Maximum particle number concentration	ca. 10 ⁷ particles/cm ³
Mass flow (particles)	ca. 10 particles/cm
iviass now (particles)	
	Type A: 8 g - 550 g/h (with reference to SAE Fine, A2 dust), Type B: 100
	- 6,000 g/h (with reference to SAE Fine, A2 dust), Type C: 350 - 7,300
	g/h (with reference to SAE Fine, A2 dust)
Particle size range	0.1 – 200 μm
Carrier/dispersion gas	
	random (generally air)
Pre-pressure	4 – 8 bar
Compressed air connection	Quick coupling
Aerosol outlet connection	Quick coupling
,	Type A: $\emptyset_{\text{inside}} = 6.4 \text{ mm}$, $\emptyset_{\text{outside}} = 10 \text{ mm}$, Type B: $\emptyset_{\text{inside}} = 8 \text{ mm}$, $\emptyset_{\text{outside}} = 12 \text{ mm}$, Type
	C: $\emptyset_{\text{inside}} = 6.2 \text{ mm}$, $\emptyset_{\text{outside}} = 10 \text{ mm}$
Reservoir volume	
	_
	1,500 cm ³
Filling quantity	
	500 a
	500 g

Version: September 3, 2020

BEG 2000 A



Applications

- Filter industry:
 - Loading test of
 - * engine filters as per ISO 5011
 - * Hot gas filters
 - * Bag filters
 - * Air filters
 - * Cyclones
 - Engine crash tests
- Chemical and pharmaceutical industry
- Cement industry

Palas GmbH

Partikel- und Lasermesstechnik Greschbachstrasse 3 b **76229 Karlsruhe**

E-Mail: mail@palas.de

Cormony

Germany

Contact:

Managing Partner: Dr.-Ing. Maximilian Weiß

Commercial Register: register court: Mannheim

company registration number: HRB 103813

USt-Id: DE143585902

Version: September 3, 2020

Internet: www.palas.de Tel: +49 (0)721 96213-0



PALASCOUNTS

Fax: +49 (0)721 96213-33