



Powder disperser with weighing unit for highest mass flows of approx. 350 g/h – 7.3 kg/h; automatic mass flow monitoring and control

Description

This dispersion system is able to continuously generate high mass flows, e.g. 7.3 kg/h, with optimal dosing constancy and control with automatic mass flow monitoring. Mass flow setting of approx. 350 g/h – 7.3 kg/h based on SAE fine, A2 dust.

BEG 2000 C



Benefits

- Excellent short-term and long-term dosing constancy
- Easy to operate
- Quick and easy to clean
- Remote control or computer-controlled
- Pulse mode
- Easy to fill while in operation
- Large reservoir (1500 cm³)
- Automatic mass flow control with the BEG 2000
- Robust design, proven in industrial applications
- Reliable function
- Reduces your operating expenses
- Low maintenance

Datasheet

Parameter	Description
Volume flow	5 – 10 m ³ /h
Power supply	115 – 230 V, 50 – 60 Hz
Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Maximum particle number concentration	ca. 10 ⁷ particles/cm ³
Mass flow (particles)	Type C: 350 – 7,300 g/h (with reference to SAE Fine, A2 dust)
Particle size range	0.1 – 200 µm
Carrier/dispersion gas	random (generally air)
Pre-pressure	4 – 8 bar
Compressed air connection	Quick coupling
Aerosol outlet connection	Type A: Ø _{inside} = 6.4 mm, Ø _{outside} = 10 mm, Type B: Ø _{inside} = 8 mm, Ø _{outside} = 12 mm, Type C: Ø _{inside} = 6.2 mm, Ø _{outside} = 10 mm
Reservoir volume	1,500 cm ³
Filling quantity	500 g

Applications

- Filter industry:
 - Loading test of
 - * engine filters as per ISO 5011
 - * Hot gas filters
 - * Bag filters
 - * Air filters
 - * Cyclones
 - Engine crash tests
- Chemical and pharmaceutical industry
- Cement industry

Palas GmbH
Partikel- und Lasermesstechnik
Greschbachstrasse 3 b
76229 Karlsruhe
Germany

Managing Partner:
Dr.-Ing. Maximilian Weiß
Commercial Register:
register court: Mannheim
company registration number: HRB 103813
USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33