



Powder disperser with weighing unit for low mass flows of approx. 8 g/h - 550 g/h; mass flow monitoring and control with automatic refill unit

### **Description**

This dispersion system is able to continuously generate low mass flows, e.g. 8 g/h, with optimal dosing constancy and control with automatic mass flow monitoring. The automatic refill unit and the weighing unit enable this dispersion system to be successfully used for continuous dosing over several days. Mass flow setting of approx. 8 g/h - 550 g/h based on SAE fine, A2 dust

Version: September 3, 2020

## **BEG 3000 A**



#### **Benefits**

- Excellent short-term and long-term dosing constancy
- Easy to operate
- Quick and easy to clean
- Remote control or computer-controlled
- Pulse mode
- Easy to fill while in operation
- Large reservoir (1500 cm<sup>3</sup>)
- Automatic mass flow control with the BEG 2000
- Long dosing time over several days with the BEG 3000
- Robust design, proven in industrial applications
- Reliable function
- Reduces your operating expenses
- Low maintenance

Version: September 3, 2020

# **BEG 3000 A**



### **Datasheet**

Parameter	Description
Volume flow	
	5 – 10 m³/h
Power supply	5 - 10 111 /11
,	
	115 – 230 V, 50 – 60 Hz
Particle material	
Desire time	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Maximum particle number concentration	Control in Control
· ·	ca. 10 <sup>7</sup> particles/cm <sup>3</sup>
Mass flow (particles)	
	Type A: 8 g - 550 g/h (with reference to SAE Fine, A2 dust)
Particle size range	0.1 – 200 μm
Carrier/dispersion gas	
_	random (generally air)
Pre-pressure	4 – 8 bar
Compressed air connection	Quick coupling
Aerosol outlet connection	Type A: $\emptyset_{\text{inside}} = 6.4 \text{ mm}$ , $\emptyset_{\text{outside}} = 10 \text{ mm}$ , Type B: $\emptyset_{\text{inside}} = 8 \text{ mm}$ , $\emptyset_{\text{outside}} = 12 \text{ mm}$ , Type
Acrosor outlet connection	C: $\emptyset_{\text{inside}} = 8 \text{ mm}$ , $\emptyset_{\text{outside}} = 12 \text{ mm}$
	C. Sinside Chimi, Soutside 12 iiiii
Reservoir volume	
	1,500 cm <sup>3</sup>
Filling quantity	15 kg

Version: September 3, 2020



## **BEG 3000 A**



### **Applications**

- Filter industry:
  - Loading test of
    - \* engine filters as per ISO 5011
    - \* Hot gas filters
    - \* Bag filters
    - \* Air filters
    - \* Cyclones
  - Engine crash tests
- Chemical and pharmaceutical industry
- Cement industry

Palas GmbH

Partikel- und Lasermesstechnik Greschbachstrasse 3 b **76229 Karlsruhe** 

Germany

Contact: E-Mail: mail@palas.de

Managing Partner:

Dr.-Ing. Maximilian Weiß Commercial Register:

register court: Mannheim company registration number: HRB 103813

USt-Id: DE143585902

Internet: www.palas.de Tel: +49 (0)721 96213-0

PALASCOUNTS

Fax: +49 (0)721 96213-33