



Version for testing filter media better than EN 779 room air filters

## Benefits

- Virtually simultaneous particle measurement in the raw gas and clean gas
- Particle size measurements from 0.2 – 40  $\mu\text{m}$
- Measurement of  $C_{n\text{ max}} = 4 \times 10^4$  particles/ $\text{cm}^3$  without dilution
- Internationally comparable measurement results
- Widespread distribution of the measurement system
- High reproducibility of the testing method
- Easy use of different test aerosols, e.g. SAE Fine and Coarse, NaCl/KCl, DEHS
- Highest raw gas concentrations of up to > 70  $\text{mg}/\text{m}^3$  (ISO Fine) or > 300  $\text{mg}/\text{m}^3$  (ISO Coarse) with measurement of the fraction separation efficiency for burden tests
- Flexible filter test software FTControl
- Sequence programs for pressure loss measurements, measurements of fraction separation efficiency and burden measurements
- Easy to operate, even untrained personnel can be instructed quickly in the use of the equipment
- Short set-up times
- Cleaning and calibration can be performed autonomously by the customer
- Easy use of the measurement technology components – even in other applications
- Mobile setup, easy to move on castors

## Applications

- Testing of filter media and small filter elements in product development and during production monitoring.
- Testing option based on ISO 16890 (General ventilation air filters), the test procedure according to ASHRAE 52.2 or EN 779 is optional available.



<https://www.palas.de/product/mfp3000g>

# MFP 3000 G



## Datasheet

Parameter	Description
Measurement range (size)	0.2 – 40 µm
Volume flow	1 – 35 m <sup>3</sup> /h (suction mode)
Dimensions	680 • 2,500 • 1,550 mm (W • H • D)
Inflow velocity	5 – 100 cm/s (others on request)
Differential pressure measurement	0 – 5,000 Pa
Test area of the medium	100 cm <sup>2</sup>
Aerosols	Dusts (e. g. SAE dusts), salts (e. g. NaCl, KCl), liquid aerosols (e. g. DEHS)
Aerosol concentrations	For SAE Fine without additional dilution up to 1,000 mg/m <sup>3</sup> (ISO A2 Fine)
Compressed air supply	6 – 8 bar

**Palas GmbH**  
Partikel- und Lasermesstechnik  
Greschbachstrasse 3 b  
**76229 Karlsruhe**  
Germany

**Managing Partner:**  
Dr.-Ing. Maximilian Weiß  
**Commercial Register:**  
register court: Mannheim  
company registration number: HRB 103813  
USt-Id: DE143585902



**Contact:** E-Mail: [mail@palas.de](mailto:mail@palas.de) Internet: [www.palas.de](http://www.palas.de) Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33