



Version for testing filter media better than ISO 5011 / ISO TS 19713 engine air filters

Description

Version MFP 3000 M is especially tailored to the requirements of the ISO 5011 and ISO TS 19713-2 measurement procedures:

Aerosol generation with RBG 1000 G: The dosing air for the RBG 1000 G solid particle aerosol generator is regulated with a mass flow controller. This ensures the same operating conditions are always maintained. solid material reservoirs and dispersing covers offer an optimal dosing time at different air volume flows.

DLB 2000 compressed air humidifier for the dispersion air: Dry compressed air is normally used for aerosol generation, whereby, at the very low volume flows in filter media testing, the rel. humidity of the test volume flow can drop considerably. The DLB 2000 compressed air humidifier can condition the rel. humidity and temperature of the RBG 1000 dispersion air precisely to the required values and thus minimises the influence of rel. humidity on the dust holding capacity to be measured.

Aerosol inlet on MFP 3000 M: The aerosol inlet on the MFP 3000 M is especially tailored to the high mass concentration of 1000 mg/m^3 and ensures a homogeneous distribution of the test aerosol in the raw gas channel. The simple construction allows the raw gas channel to be easily cleaned.

welas® 2070 aerosol sensors: The welas® 2070 high concentration sensors ensure unambiguous and coincidence-free fractional separation efficiency measurement at the high concentration of 1000 mg/m^3 . These sensors are also fitted with a special aerosol guide that minimises contamination of the internal optics.

Software: Various differential pressure levels can be set in the filter media test sequence program for loading in accordance with ISO 5011. The clear definition of the test parameters in the pre-programmable sequence programs ensure very high level comparability of the results.

Benefits

- Virtually simultaneous particle measurement in the raw gas and clean gas
- Particle size measurements from 0.2 – 40 µm
- Measurement of $C_{n\max} = 10^6$ particles/cm³ without dilution
- Internationally comparable measurement results
- Widespread distribution of the measurement system
- High reproducibility of the testing method
- Easy use of different test aerosols, e.g. SAE Fine and Coarse, NaCl/KCl, DEHS
- Highest raw gas concentrations of up to > 1000 mg/m³ (ISO Fine) or > 5000 mg/m³ (ISO Coarse) with measurement of the fraction separation efficiency for burden tests
- Flexible filter test software FTControl
- Sequence programs for pressure loss measurements, measurements of fraction separation efficiency and burden measurements
- Easy to operate, even untrained personnel can be instructed quickly in the use of the equipment
- Short set-up times
- Cleaning and calibration can be performed autonomously by the customer
- Easy use of the measurement technology components – even in other applications
- Mobile setup, easy to move on castors
- Reliable operation
- Validation of the clear function of individual components and the overall system during pre-delivery acceptance testing and upon delivery
- Low-maintenance
- The unit will reduce your operating costs

Datasheet

<i>Parameter</i>	<i>Description</i>
Measurement range (size)	0.2 – 40 µm
Volume flow	1 – 35 m ³ /h (suction mode)
Dimensions	680 • 2,500 • 1,550 mm (W • H • D)
Inflow velocity	5 – 100 cm/s (others on request)
Differential pressure measurement	0 – 5,000 Pa
Test area of the medium	100 cm ²
Aerosols	Dusts (e. g. SAE dusts), salts (e. g. NaCl, KCl), liquid aerosols (e. g. DEHS)
Aerosol concentrations	For SAE Fine without additional dilution up to 1,000 mg/m ³ (ISO A2 Fine)
Compressed air supply	6 – 8 bar

Applications

- Testing of filter media and small filter elements in product development and during production monitoring.
- Testing based on ISO 5011 (engine air intake filters)

Palas GmbH
Partikel- und Lasermesstechnik
Greschbachstrasse 3 b
76229 Karlsruhe
Germany

Managing Partner:
Dr.-Ing. Maximilian Weiß
Commercial Register:
register court: Mannheim
company registration number: HRB 103813
USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33