



With automatic regulation of sampling volume flow by the aerosol sensors *welas*® under overpressure up to 10 bar or in temperatures to 120 °C

Description

Depending on the composition of the aerosol to be measured, i.e. the carrier gas component and the particle material, pressure and temperature changes in the carrier gas can significantly influence the particle size distribution, e.g. due to condensation or evaporation. For this reason, the *welas*® aerosol sensors *welas*® 1100 HP and *welas*® 1200 HP are equipped with a cuvette heatable up to 120 °C and pressure-tight up to 10 barg to ensure isobaric and isothermal sampling into the sensor's measurement volume.

welas® digital is usually calibrated for the operating volume flow. As the operating volume flow changes with pressure and temperature, it is advantageous for the user if automatic volume flow regulation for the sampling volume flow is provided for in the device.

the Promo® 1000 HP the pressure and temperature of the carrier gas are measured and the required operating volume flow is automatically set to 5 l/min.

:

- Mass flow controller for volume flow regulation
- Heating regulator up to 120 °C
- Temperature sensor
- Absolute pressure capsule
- Filter unit

Benefits

- Measuring range of 200 nm to 40 µm (3 measuring ranges selectable in one device)
- Up to three measuring ranges in only one device:
 - 0.2 µm – 10 µm
 - 0.3 µm – 17 µm
 - 0.6 µm – 40 µm
- Up to 128 size channels per measuring range
- Concentration range from < 1 particle/cm³ to 5 • 10⁵ particles/cm³
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency rate starting at 0.2 µm
- High temporal resolution down to 10 ms
- Analysing software PDAnalyze
- Calibration, cleaning and lamp replacement can all be performed independently by the customer
- External control via RS 232 or Ethernet
- Optional: PDControl software for operation as welas[®] digital

- Simple operation
- Low maintenance
- Reliable function
- Reduces your operating expenses

Datasheet

Parameter	Description
Interfaces	USB, Ethernet, RS232/485, Wi-Fi
Measurement range (size)	0.2 – 10 µm, 0.3 – 17 µm, 0.6 – 40 µm
Size channels	up to 128 (64/decade)
Measuring principle	Optical light-scattering
Measurement range (number C_N)	< 5 • 10 ⁵ particles/cm ³
Time resolution	up to 1 s
Thermodynamic conditions	10 – 120 °C, 2 – 10 bar _g
Volume flow	5 l/min, 1.6 l/min
Data acquisition	20 MHz processor, 256 raw data channels, digital
Light source	Xenon high pressure lamp 75 W
User interface	Touch screen, 800 • 480 pixels, 7" (17.78 cm)
Power supply	115 – 230 V, 50 – 60 Hz
Housing	Table housing, optionally with mounting brackets for rack-mounting
Dimensions	185 • 450 • 315 mm (H • W • D) (19")
Weight	approx. 8 kg (control unit), 18 kg (sensor)
Operating system	Windows embedded
Data logger storage	4 GB Compact Flash
Software	PDCControl, FTControl
Installation conditions	+5 – +40 °C (control unit)

Applications

- Abscheidegradbestimmung von KFZ Innenraumfiltern, Motorluftfiltern, Raumluftfiltern, Druckluftfiltern, Staubsaugerfiltern, abreinigbaren Filtern, Elektrofiltern, Ölabscheidern, Kühlschmierstoffabscheidern, Nassabscheidern, Zyklonen und anderen Abscheidern
- Isotherme und isobare Partikelgrößen- und Mengenbestimmung, z. B. in der Automobil-, Chemie-, Pharma- und Lebensmittelindustrie
- Untersuchung schneller, instationärer Prozesse
- Partikelmessung zur Wolkenbildung
- Emissionsmessungen

Palas GmbH
Partikel- und Lasermesstechnik
Greschbachstrasse 3 b
76229 Karlsruhe
Germany

Managing Partner:
Dr.-Ing. Maximilian Weiß
Commercial Register:
register court: Mannheim
company registration number: HRB 103813
USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33