



With automatic regulation of the sampling flow through the welas[®] aerosol sensors at an overpressure of 2 to 10 bar or in temperatures up to 120 °C

Benefits

- Measuring range of 0.2 to 100 µm (4 measuring ranges selectable in one device)
- Up to four measuring ranges in only one device:
 - 0,2 µm – 10 µm
 - 0,3 µm – 17 µm
 - 0,6 µm – 40 µm
 - 2 µm – 100 µm (additionally for sensors 2300 and 2500)
- Up to 128 size channels per measuring range
- Concentration range of 1 particle/cm³ to 10⁶ particles/cm³
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency rate starting at 0.2 µm
- **Pressure-resistant up to 10 bar (optional)**
- **Heatable to 250 °C (optional)**
- Optical fibre technology
- Simple operation with a large touch display
- Calibration, cleaning and lamp replacement can all be performed independently by the customer
- External control by RS 232 or Ethernet
- With analysis software PDAnalyze
- Optional: Software PDControl for operation as welas[®] digital available

Applications

- Emission monitoring of installations
- Control of grinding and classification processes
- Monitoring of production processes in the food, pharmaceuticals and chemicals industries
- Testing of complete filters, inertial and wet separators or electrostatic precipitators



<https://www.palas.de/product/promo2000hp>

Datasheet

Parameter	Description
Interfaces	USB, Ethernet, RS232/485, Wi-Fi
Measurement range (size)	0,2 µm – 10 µm, 0,3 µm – 17 µm, 0,6 µm – 40 µm, 2 µm – 100 µm
Size channels	up to 128 (64/decade)
Measuring principle	Optical light-scattering
Measurement range (number C_N)	< 1 • 10 ⁶ particles/cm ³
Volume flow	5 l/min
Data acquisition	20 MHz processor, 256 raw data channels, digital
Light source	Xenon arc lamp 35 W
Power consumption	100 W
User interface	Touch screen, 800 • 480 pixel, 7"
Housing	Table housing, optionally with mounting brackets for rack-mounting
Dimensions	185 • 450 • 315 mm (H • W • D) (19")
Support options	Direct remote access, Palas® webserver service
Weight	approx. 8 kg (control unit), approx. 2.8 kg (sensor)
Operating system	Windows embedded
Data logger storage	4 GB Compact Flash
Software	PDControl, FTControl, PDAnalyze
Installation conditions	+5 – +40 °C (control unit)

Palas GmbH
Partikel- und Lasermesstechnik
Greschbachstrasse 3 b
76229 Karlsruhe
Germany

Managing Partner:
Dr.-Ing. Maximilian Weiß
Commercial Register:
register court: Mannheim
company registration number: HRB 103813
USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33