



With automatic regulation of the sampling flow through the *welas[®]* aerosol sensors at an overpressure up to 10 bar

Benefits

- Measuring range of 0.2 to 100 μm (up to 4 measuring ranges selectable in one device)
- Up to four measuring ranges in only one device:
 - 0,2 μm – 10 μm
 - 0,3 μm – 17 μm
 - 0,6 μm – 40 μm
 - 2 μm – 100 μm (additionally for sensors 2300 and 2500)
- Up to 128 size channels per measuring range
- Concentration range of 1 particle/ cm^3 to 10^6 particles/ cm^3
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency rate starting at 0.2 μm
- **Pressure-resistant up to 10 bar (optional)**
- Optical fibre technology
- Simple operation with a large touch display
- Calibration, cleaning and lamp replacement can all be performed independently by the customer
- External control by RS 232 or Ethernet
- With analysis software PDAnalyze
- Optional: Software PDControl for operation as *welas[®]* digital available
- Low maintenance

Applications

- Emission monitoring of installations
- Control of grinding and classification processes
- Monitoring of production processes in the food, pharmaceuticals and chemicals industries
- Testing of complete filters, inertial and wet separators or electrostatic precipitators



<https://www.palas.de/product/promo2000p>

Datasheet

Parameter	Description
Interfaces	USB, Ethernet, RS232/485, Wi-Fi
Measurement range (size)	0,2 µm – 10 µm, 0,3 µm – 17 µm, 0,6 µm – 40 µm, 2 µm – 100 µm
Size channels	up to 128 (64/decade)
Measuring principle	Optical light-scattering
Measurement range (number C_N)	< 1 • 10 ⁶ particles/cm ³
Volume flow	5 l/min regulated by mass flow
Data acquisition	20 MHz processor, 256 raw data channels, digital
Light source	Xenon arc lamp 35 W
Power consumption	100 W
User interface	Touch screen, 800 • 480 pixel, 7"
Housing	Table housing, optionally with mounting brackets for rack-mounting
Dimensions	185 • 450 • 315 mm (H • W • D) (19")
Support options	Direct remote access, Palas [®] webserver service
Weight	approx. 8 kg (control unit), approx. 2.8 kg (sensor)
Operating system	Windows embedded
Data logger storage	4 GB Compact Flash
Software	PDControl, FTControl, PDAnalyze
Installation conditions	+5 – +40 °C (control unit)

Palas GmbH
 Partikel- und Lasermesstechnik
 Greschbachstrasse 3 b
76229 Karlsruhe
 Germany

Managing Partner:
 Dr.-Ing. Maximilian Weiß
Commercial Register:
 register court: Mannheim
 company registration number: HRB 103813
 USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33