



Dispersing unit removable and weighable

## Description

This version is equipped with special dispersion covers (type A, type B) and special solid material reservoirs with diameters of 7, 10, and 14 mm.



Fig. 1: Removable and weighable dispersing unit

RBG 1000				
Reservoir ∅	Fill quantity	Feed rate 1 mm/h	Feed rate 5 mm/h	Feed rate 700 mm/h
7 mm	2.7 g	38 mg/h	190 mg/h	27 g/h
10 mm	5.5 g	79 mg/h	395 mg/h	55 g/h
14 mm	10.8 g	154 mg/h	770 mg/h	107 g/h
20 mm	22 g	314 mg/h	1570 mg/h	219 g/h
28 mm	43 g	616 mg/h	3080 mg/h	430 g/h
RBG 2000				
16 mm	36 g	0.2 g/h	1 g/h	140 g/h
20 mm	56 g	0.3 g/h	1.5 g/h	220 g/h
28 mm	110 g	0.6 g/h	3 g/h	430 g/h
32 mm	144 g	0.8 g/h	4 g/h	562 g/h

Table 1: Mass flows of RBG system (compacted density 1 g/cm<sup>3</sup>)

	Particle size	Reservoir ∅	Volume flows
Cover A	<0,1–100 µm	7-32 mm	2–5 m <sup>3</sup> /h
Cover B	<0,1–100 µm	7, 10 and 14 mm	1–2.5 m <sup>3</sup> /h
Cover C	<0.1–100 µm	7 mm	0.5–1.2 m <sup>3</sup> /h
Cover D	200–1000 µm	7-32 mm	2–5 m <sup>3</sup> /h

Table 2: Dispersion covers

	Feed rate mm/h	Reservoir Ø mm	Reservoir length mm
RBG 1000	700	7-28	70
RBG 1000 D	700	7-20	70
RBG 1000 G	300	7-28	70
RBG 1000 GD	300	7-20	70
RBG 1000 L	700	10, 14	70
RBG 1000 SD	700	7-20	70
RBG 1000 SG	300	7-20	70
RBG 1000 I	700	7-28	70
RBG 1000 ID	700	7-20	70
RBG 1000 ISD	700	7-20	70
RBG 2000	700	16 - 32	180
RBG 2000 D	700	16, 20, 28	180
RBG 2000 SD	700	16, 20, 28	180

Table 3: Different versions of the RBG system I = version for inhalation= pressure-resistant= low feed rate= easily removable and weighable dosing unit= nitrogen version

## Benefits

- **Dispersing unit can be removed and weighed**
- **Optional: Remote control or computer-controlled**
- Highest short-term and long-term dosing constancy
- Disperses virtually all non-cohesive dusts
- Easy exchange of different solid material reservoirs and dispersing covers
- Easy determination and adjustment of the mass flow
- Pulse mode
- Device easy to clean
- Quick and easy to operate
- Reliable operation
- Little maintenance required
- Reduces your operating expenses

## Datasheet

Parameter	Description
Volume flow	0.5 – 5.0 m <sup>3</sup> /h
Power supply	115/230 V, 50 – 60 Hz
Dimensions	465 • 320 • 200 mm (H • W • D)
Weight	approx. 19 kg
Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Maximum particle number concentration	ca. 10 <sup>7</sup> particles/cm <sup>3</sup>
Mass flow (particles)	0.04 – 430 g/h (with an assumed compacted density of 1 g/cm <sup>3</sup> )
Particle size range	0.1 – 100 µm
Carrier/dispersion gas	random (generally air)
Pre-pressure	4 – 8 bar
Feed rate	5 – 700 mm/h
Reservoir diameter	7, 10, 14 mm
Maximum counter pressure	200 mbar <sub>g</sub>
Reservoir length	70 mm
dispersion cover	Type A, type B
Compressed air connection	Quick coupling
Aerosol outlet connection	Dispersion cover type A: Ø <sub>inside</sub> = 5 mm, Ø <sub>outside</sub> = 8 mm; Dispersion cover type B: Ø <sub>inside</sub> = 3.6 mm, Ø <sub>outside</sub> = 6 mm; Dispersion cover type: Ø <sub>inside</sub> = 2.5 mm, Ø <sub>outside</sub> = 6 mm
Filling quantity	2.7 g (reservoir Ø = 7 mm), 5.5 g (reservoir Ø = 10 mm), 10.8 g (reservoir Ø = 14 mm), 22 g (reservoir Ø = 20 mm), 43 g (reservoir Ø = 28 mm)

## Applications

- Filter industry:
  - Determination of fractional separation efficiency
  - Determination of total separation efficiency
  - Long-term dusting
  - Filter media and ready-made filters
  - Dust removal filters
  - Vacuum cleaners and vacuum cleaner filters
  - Car interior filters
  - Engine air filters
- Calibration of particle measurement devices
- Flow visualization
- Inhalation tests
- Tracer particles for LDA, PIV, etc.
- Coating of surfaces

**Palas GmbH**  
Partikel- und Lasermesstechnik  
Greschbachstrasse 3 b  
**76229 Karlsruhe**  
Germany

**Managing Partner:**  
Dr.-Ing. Maximilian Weiß  
**Commercial Register:**  
register court: Mannheim  
company registration number: HRB 103813  
USt-Id: DE143585902



**Contact:** E-Mail: [mail@palas.de](mailto:mail@palas.de) Internet: [www.palas.de](http://www.palas.de) Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33