



Pressure-resistant at positive pressure values of up to 3 bar, higher mass flows

Benefits

- **Pressure-resistant at positive pressure values of up to 3 bar**
- Optimal short-term and long-term dosing constancy
- Double the dosing time in comparison with the RBG 1000
- Disperses virtually any non-cohesive dusts
- Easy to switch out different solid material reservoirs and dispersion covers
- Easy to determine and adjust the mass flow
- Able to adjust higher mass flows than the RBG 1000
- Pulse mode
- Easy to clean
- Quick and easy to operate
- Reliable function
- Low maintenance
- Reduces your operating expenses

Applications

- **Alle Anwendungen druckfest bis 3 bar Überdruck**
- **Testen von Druckluftfiltern**
- Filter industry
 - Determination of fractional separation efficiency
 - Determination of total separation efficiency
 - Long-term dusting
 - Filter media and assembled filters
 - Dust filters
 - Vacuum cleaners and vacuum filters
 - Car interior filters
 - Engine air filters
- Calibrating particle measurement devices
- Flow visualization
- Inhalation experiments
- Tracer particles for LDV, PIV, etc.
- Surface coatings



<https://www.palas.de/product/rbg2000d>

Datasheet

Parameter	Description
Volume flow	2.5 – 5.0 m ³ /h
Power supply	115/230 V, 50 – 60 Hz
Dimensions	1,160 • 530 • 500 mm (H • W • D)
Weight	approx. 40 kg
Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Maximum particle number concentration	ca. 10 ⁷ particles/cm ³
Mass flow (particles)	1 – 560 g/h (with an assumed compacted density of 1 g/cm ³)
Particle size range	0.1 – 100 µm
Carrier/dispersion gas	Air
Pre-pressure	4 – 8 bar
Feed rate	5 – 700 mm/h
Reservoir diameter	16, 20, 28 mm
Maximum counter pressure	up to 3 bar _g overpressure
Reservoir length	180 mm
dispersion cover	Type A, type D
Compressed air connection	Quick coupling
Aerosol outlet connection	Dispersion cover type A: Ø _{inside} = 5 mm, Ø _{outside} = 8 mm; Dispersion cover type D: Ø _{inside} = 5 mm, Ø _{outside} = 8 mm
Filling quantity	36 g (reservoir Ø = 16 mm), 56 g (reservoir Ø = 20 mm), 110 g (reservoir Ø = 28 mm), 144 g (reservoir Ø = 32 mm)

Palas GmbH

Partikel- und Lasermesstechnik
Greschbachstrasse 3 b
76229 Karlsruhe
Germany

Managing Partner:

Dr.-Ing. Maximilian Weiß

Commercial Register:

register court: Mannheim
company registration number: HRB 103813
USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33