

U-RANGE 2000



Useful combination of the Fidas® and U-SMPS systems for particle measurements in the size range of 8 nm to 40 µm

Benefits

- Particle size distributions from 8 to 40 nm
- Additional determination of PM fractions (e.g. PM_{2.5}, PM₁₀)
- Continuous and fast-scanning principle of measurement
- High resolution in up to 64 size classes/decade
- Graphic display of measurement values
- Intuitive operation using 7" touchscreen and GUI
- Integrated data logger
- Supports multiple interfaces and remote access
- Low maintenance
- Reliable function
- Reduces your operating expenses

Applications

- Aerosol research
- Environmental and climatic studies
- Inhalation experiments
- Filter test
- Interior and workplace measurements
- Distribution studies (e.g. fires, volcanoes)



<https://www.palas.de/product/urange2000>

U-RANGE 2000



Datasheet

Parameter	Description
Interfaces	USB, Ethernet, Wi-Fi, RS-232/485
Size channels	up to 120 (32/decade)
Time resolution	3 min.
Volume flow	4.8 l/min
User interface	Touch screen, 800 • 480 pixel, 7"
Power supply	115/230 V, 50/60 Hz
Dimensions	19" or 18.5 • 45 • 32 cm (H • W • D, Fidas®), 33 • 38 • 24 cm (H • W • D, UF-CPC), 15 • 57 cm (ø base • H, U-SMPS column), 33 • 38 • 24 cm (H • W • D, U-SMPS control unit)
Weight	Approx. 9.3 kg (Fidas®, U-SMPS column), approx. 12.9 kg (U-SMPS control unit), approx. 10 kg (U-SMPS UF-CPC)
Data logger storage	4 GB
Software	PDAnalyze
Volume flow (sheath air)	2.5 – 10 l/min
Operation liquid	Butanol, isopropanol, water or other (UF-CPC)
Particle size range	8 – 40,000 nm

Palas GmbH
Partikel- und Lasermesstechnik
Greschbachstrasse 3 b
76229 Karlsruhe
Germany

Managing Partner:
Dr.-Ing. Maximilian Weiß
Commercial Register:
register court: Mannheim
company registration number: HRB 103813
USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33