



Powerful aerosol spectrometer with the highest particle size resolution, **measuring range from 120 nm to 40 µm**

## Benefits

- Four measuring ranges in only one device:
  - 0.12 µm – 3.5 µm
  - 0.2 µm – 10 µm
  - 0.3 µm – 17 µm
  - 0.6 µm – 40 µm
- Up to 128 size channels per measuring range
- Concentration range from < 1 particle/cm<sup>3</sup> to 5 • 10<sup>5</sup> particles/cm<sup>3</sup>
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency rate starting at 0.12 µm
- High temporal resolution down to 10 ms
- Extensive PDControl and FTControl software
- Strong, powerful external suction pump ASP 1000
- Calibration, cleaning and lamp replacement can all be performed independently by the customer
- Simple operation
- Low maintenance
- Reliable function
- Reduces your operating expenses

## Applications

- Determination of the separation efficiency of car interior filters, engine air filters, room air filters, compressed air filters, vacuum cleaner filters, cleanable filters, electrostatic precipitators, oil separators, cooling lubricant separators, wet scrubbers, cyclones and other separators
- Isothermal and isobaric particle size and quantitative determination, for instance in the automobile, chemical, pharmaceutical and food industries
- Analysis of fast, transient processes
- Inspection of smoke detectors
- Particle formation for cloud formation

## Model Variations

model available in additional variations  
...more variations available



<https://www.palas.de/product/welasdigital1000>

## Datasheet

Parameter	Description
<b>Interfaces</b>	USB
<b>Measurement range (size)</b>	0.12 µm – 3.5 µm, 0.2 µm – 10 µm, 0.3 µm – 17 µm, 0.6 µm – 40 µm
<b>Size channels</b>	up to 64/decade
<b>Measuring principle</b>	Optical light-scattering
<b>Measurement range (number C<sub>N</sub>)</b>	< 5 • 10 <sup>5</sup> particles/cm <sup>3</sup>
<b>Time resolution</b>	≥ 10 ms
<b>Thermodynamic conditions</b>	10 – 40 °C, -100 – 50 mbar
<b>Volume flow</b>	5 l/min, 1.6 l/min
<b>Data acquisition</b>	20 MHz processor, 256 raw data channels, digital
<b>Light source</b>	Xenon high pressure lamp 75 W
<b>User interface</b>	Laptop
<b>Power supply</b>	115 – 230 V, 50 – 60 Hz
<b>Housing</b>	Table housing, optionally with mounting brackets for rack-mounting
<b>Dimensions</b>	185 • 450 • 315 mm (H • W • D) (19")
<b>Weight</b>	approx. 8 kg (control unit), approx. 18 kg (sensor)
<b>Software</b>	PDControl, FTControl
<b>Installation conditions</b>	+5 – +40 °C (control unit)

**Palas GmbH**  
 Partikel- und Lasermesstechnik  
 Greschbachstrasse 3 b  
**76229 Karlsruhe**  
 Germany

Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33

**Managing Partner:**  
 Dr.-Ing. Maximilian Weiß  
**Commercial Register:**  
 register court: Mannheim  
 company registration number: HRB 103813  
 USt-Id: DE143585902

