



With heating regulation up to 120 °C for welas[®] aerosol sensors

Benefits

- Three measuring ranges in only one device:
 - 0.2 µm – 10 µm
 - 0.3 µm – 17 µm
 - 0.6 µm – 40 µm
- Up to 128 size channels per measuring range
- Concentration range from < 1 particle/cm³ to 5 • 10⁵ particles/cm³
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency rate starting at 0.2 µm
- High temporal resolution down to 10 ms
- Extensive PDControl and FTControl software
- Strong, powerful external suction pump ASP 1000
- Calibration, cleaning and lamp replacement can all be performed independently by the customer
- Simple operation
- Low maintenance
- Reliable function
- Reduces your operating expenses

Applications

- Determination of the separation efficiency of car interior filters, engine air filters, room air filters, compressed air filters, vacuum cleaner filters, cleanable filters, electrostatic precipitators, oil separators, cooling lubricant separators, wet scrubbers, cyclones and other separators
- Isothermal and isobaric particle size and quantitative determination, for instance in the automobile, chemical, pharmaceutical and food industries
- Analysis of fast, transient processes
- Inspection of smoke detectors
- Particle formation for cloud formation
- Emission measurements
- Immission measurements



<https://www.palas.de/product/welasdigital1000h>

Datasheet

Parameter	Description
Interfaces	USB
Measurement range (size)	0.2 - 10 µm, 0.3 - 17 µm, 0.6 - 40 µm
Size channels	up to 64/decade
Measuring principle	Optical light-scattering
Measurement range (number C_N)	< 5 • 10 ⁵ particles/cm ³
Time resolution	≥ 10 ms
Thermodynamic conditions	10 - 40 °C, -100 - 50 mbar
Volume flow	5 l/min, 1.6 l/min
Data acquisition	20 MHz processor, 256 raw data channels, digital
Light source	Xenon high pressure lamp 75 W
User interface	Laptop
Power supply	115 - 230 V, 50 - 60 Hz
Housing	Table housing, optionally with mounting brackets for rack-mounting
Dimensions	185 • 450 • 315 mm (H • W • D) (19")
Weight	approx. 8 kg (control unit), approx. 18 kg (sensor)
Software	PDControl, FTControl
Installation conditions	+5 - +40 °C (control unit)

Palas GmbH
Partikel- und Lasermesstechnik
Greschbachstrasse 3 b
76229 Karlsruhe
Germany

Managing Partner:
Dr.-Ing. Maximilian Weiß
Commercial Register:
register court: Mannheim
company registration number: HRB 103813
USt-Id: DE143585902



Contact: E-Mail: mail@palas.de Internet: www.palas.de Tel: +49 (0)721 96213-0 Fax: +49 (0)721 96213-33